

## Spray And Walk Away



**Covalent Bonding** 



Single Component



Anti Graffiti



Extreme Hardness



**UV** Stable



Spray Applied

Coval Ultimate Top Coat is a thin-film, single component coating designed to protect finished surfaces and decorative coatings from surface wear and harsh chemicals. It creates a covalent bond with the coating substrate and is easily and quickly applied with an acetone pump sprayer. UTC is used over epoxy, terrazzo, polished, stained, or sealed concrete floors and counter-tops.

Ultimate Top Coat provides a sustainable solution. It reduces maintenance and is easy to clean, eliminating the need for guards, strippers, waxes, and harsh cleaning chemicals.

Coval coatings contain less than 100 g/L VOCs and exceed SCAQMD Rule 1113 requirements for air quality; as well as contain no known carcinogens under Proposition 65, California's Drinking Water and Toxic Enforcement Act of 1986.











**Epoxy:** The spray down application of Coval UTC allows for more efficient installations over epoxy, providing superior abrasion and chemical resistance over urethanes and polyaspartics without the need for backrolling.



Polished Concrete: Coval UTC is non-sacrificial, providing a lasting barrier against stains and etching that do not require harsh chemicals to clean up.



**Terrazzo:** Eliminate maintenance time and materials costs with Coval UTC. The high gloss shine will last for years in high traffic areas with no need for buffing.

Resin System	Component	Tack Free Time	Hardness D3363	Abrasion D4060	Surface Prep	Adhesion
Coval Hybrid	1K	2-3 h	9H	<1 @ 7 Day cure	Clean Surface	Covalent Bond
Polyaspartic	2K	6-8 h	4H	61 @ 7 Day Cure	Profile required	Physical/Charge
Ероху	2K	24 h	6H	44 @ 7 Day Cure	Profile required	Physical/Charge
Polyurethane	2K	24 h	6H	2 @ 30 Day Cure	Profile required	Physical